

Procoil

Premium Quality Manufacturing Process Oil

Procoil lubricants are a range of straight mineral oils, their prime uses being for other than lubrication. They are used in the manufacturing process where they may, or may not, form a component of the finished product and where their chemical composition may be of particular importance.

Summary of Benefits

- *Uniform Characteristics* Uniformity of physical and chemical characteristics of the series ensures satisfactory application of oils.
- *Wide range* Range of viscosities permits wide flexibility and use in any finished products.

Application

Procoil is a paraffinic oil range often used in the rubber, plastics and adhesives industries. *Procoil* is suitable for use as carrier oils in chemical processing, diluent of additives, dust control and as extenders in the compounding of rubber, plastics and adhesives.

Product Code: 7048-7050

Product Size: Various

Procoil

Typical Characteristics:

ISO Grade	22	32	46
Specific Density at 15°C (kg/L)	0.855	0.865	0.87
Kinematic Viscosity at 40°C mm ² /s (cSt)	21	30	45.5
Kinematic Viscosity at 100°C mm ² /s (cSt)	4.5	5.1	6.8
Viscosity Index	100	98	98
Flash Point OCO (°C)	206	210	220

*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.

Storage:

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment

A Material Safety Data Sheet (MSDS) is available for each product. Users should consult the MSDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Materials Safety Data Sheet is available at Royal Precision Lubricants by email: info@royallubricants.com.au.